



Optical and Wireless Technologies pp 311–319

[Home](#) > [Optical and Wireless Technologies](#) > Conference paper

Dispersion Engineered AsSe₂ Based Chalcogenide Photonic Crystal Fiber for MIR Region Supercontinuum Generation

[Vaibhav Gupta](#), [Jaiverdahan](#), [Vinay Kanungo](#), [Rukhsar Zafar](#), [Sandeep Vyas](#), [Anand Nayyar](#) & [Ghanshyam Singh](#)

Conference paper | [First Online: 02 September 2021](#)

929 Accesses | **2** Citations

Part of the [Lecture Notes in Electrical Engineering](#) book series (LNEE, volume 771)

Abstract

A highly nonlinear chalcogenide glasses have been studied in this paper for a broadening supercontinuum generation. This research demonstrates the generation of supercontinuum expanding from 1000 nm to over 15,000 nm through pumping pulse of peak power 5 kW in an extremely nonlinear AsSe₂ based chalcogenide microfiber. The conventional ring-shaped air vents in the cladding region are improved by fitting elliptical air vents in the second ring of the proposed microfiber design. The geometrical parameters of the modeled design of the fiber are selected to instate a flat and broad profile of dispersion in the anomalous region. The reported photonic crystal fiber shape propose a very large nonlinearity of 1522 W⁻¹ km⁻¹ with low and flattened dispersion at 3.9 μm pump wavelength. The effective mode

Anand Nayyar

Faculty of Information Technology,
Duy Tan University, Da Nang, Viet
Nam

[View author publications](#)

You can also search for this author
in
[PubMed](#) | [Google Scholar](#)