



PAPER • OPEN ACCESS

Feasibility Evaluation and Numerical Simulation of Diesel–Diethyl Ether–2–Methoxy Ethyl Ether Blends Fueling in Stationary CI Engine

Mukesh Kumar, Chandan Kumar, Umesh Kumar Das and Sumit Sharma

Published under licence by IOP Publishing Ltd

IOP Conference Series: Earth and Environmental Science, Volume 1279, Third International Conference on Sustainable Energy, Environment and Green Technologies (ICSEEGT 2023) 27/06/2023 - 28/06/2023 Jaipur, India

Citation Mukesh Kumar *et al* 2023 *IOP Conf. Ser.: Earth Environ. Sci.* **1279** 012014

DOI 10.1088/1755-1315/1279/1/012014

[Buy this article in print](#)

 Journal RSS

 Sign up for new issue notifications

Abstract

In many developed economies, the diesel engine is very important for transportation and farming. There is a lot of research being done in the field of renewable energy to replace conventional energy sources because of the major environmental issues and the rising expense of diesel. Diesel engine cannot be reinstated because of its efficient performance at higher power and reliability with alternative engines. Diesel engine emissions are very harmful to the atmosphere and human health. The main contaminants in diesel engines are smoke and NO_x, which need to be effectively monitored. A numerous research is going on to diminish the emissions from CI engines by using some additives as well as the use of alternative fuels. This

experimental inquiry was conducted to identify a suitable addition to lower exhaust emissions and improve CI engine performance. The trials used various mix ratios of pure diesel and blends of diesel and diethyl ether-2-methoxy ethyl ether. Mixing of 5% DEE and 5% MXEE with 90% diesel on volume basis (D90–DEE5–MXEE5) showed optimum results of emission and performance. Low exhaust emissions (HC 63.15%, CO 60.00%, and Smoke 18.29%) found to be substantial at peak loads and performance increase (decreasing in BSFC 5.00% and increasing in BTE 3.00%) were compared to mixture D90-DEE5-MXEE5 with diesel (at standard engine conditions). However, NO_x rises (2.60%).

Export citation and abstract

BibTeX

RIS

← **Previous** article in issue

Next article in issue →



Content from this work may be used under the terms of the [Creative Commons Attribution 3.0 licence](#). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

You may also like

JOURNAL ARTICLES

Development of a bi-fuel power supply system for a diesel engine

Comparison of properties of ternary fuel blends of diesel-octanol with biodiesel

Health Condition Identification and Quantitative Assessment of Emergency Diesel Generator Sets Based on Back Propagation Neural Network and Mahalanobis Distance

DI-diesel engine fueled with orange peel calophyllum seed blended biodiesel

Crude Castor Oil as Blend Component in Diesel/Ethanol Fuel Blend: Combustion Characteristics and Exhaust Emissions

Improving the fuel supply process of diesel locomotive

IOPSCIENCE

Journals

Books

IOP Conference Series

About IOPscience

Contact Us

Developing countries access

IOP Publishing open access policy

Accessibility

IOP PUBLISHING

Copyright 2024 IOP Publishing

Terms and Conditions

Disclaimer

Privacy and Cookie Policy

Text and Data mining policy

PUBLISHING SUPPORT

Authors

Reviewers

Conference Organisers



This site uses cookies. By continuing to use this site you agree to our use of cookies.

