

Materials Today: Proceedings  
Volume 44, Part 6, 2021, Pages 4784-4788

## Optimization of sliding and mechanical performance Ti/Ni metal powder particulate reinforced Al 6061 alloy composite using preference selection index method

Ashiwani Kumar <sup>a</sup> ✉, Mukesh Kumar <sup>b</sup>, Amar Patnaik <sup>b</sup>, M.J. Pawar <sup>c</sup>, Akhileshwar Pandey <sup>d</sup>, Anil Kumar <sup>e</sup>, Vikas Gautam <sup>f</sup>

<sup>a</sup> Mechanical Engg. Dept., Feroze Gandhi Institute of Engg. & Tech., Rae Bareilly, U.P. 229316, India

<sup>b</sup> Mechanical Engg. Dept., Malaviya National Institute of Tech., Jaipur, Rajasthan 302017, India

<sup>c</sup> Mechanical Engg. Dept., K.J. Somaiya College of Engineering, Mumbai 400007, India

<sup>d</sup> Mechanical Engg. Dept., Government Engineering College, Bharatpur 321001, India

<sup>e</sup> Mechanical Engg. Dept., Kamla Nehru Institute of Technology, Sultanpur 228118, India

<sup>f</sup> Mechanical Engg. Dept., Swami Keshvanand Institute of Technology Management & Gramothan, 302021, India

Received 21 September 2020, Revised 14 October 2020, Accepted 24 October 2020, Available online 21 January 2021.

Show less ^

☰ Outline | 🔗 Share 🗣️ Cite

<https://doi.org/10.1016/j.matpr.2020.10.974>

Get rights and content

### Abstract

In this study, Ti/ Ni reinforced in AA6061 composites were prepared via a high vacuum stir casting method. The fabricated composite specimens are prepared for experimental studies as per ASTM standard and then physical, mechanical, and sliding wear characterization was conducted on different equipment. The higher confidence level (95%) obtained via experimental studies. The experimental results of the specimen have been used for optimization, and the ranking order of composite are computed via using the preference selection index method. Many researchers' results have been reported and easily computed to rank of composite composition using optimization properties such as void contents, density flexural strength, tensile strength, impact strength, wear resistance etc. The results reveal that the base matrix included with the equal presence of both particulates exhibits most excellent properties hence to obtained best ranked of



Materials Today: Proceedings

Volume 46, Part 15, 2021, Pages 6534-6540

# Investigation on mechanical and tribological characterization of Gr filled AA7075 alloy composite using Taguchi method

Ashiwani Kumar <sup>a</sup> , Mukesh Kumar <sup>b</sup>, Vikas Kukshal <sup>c</sup>, Akhileshwar Pandey <sup>d</sup>, M.J. Pawar <sup>e</sup>, Vikash Gautam <sup>f</sup>

- <sup>a</sup> Mechanical Engineering Department, Feroze Gandhi Institute of Engineering and Technology, Raebareli 2299316, UP, India
- <sup>b</sup> Mechanical Engineering Department, Malaviya National Institute of Technology, Jaipur 302017, Rajasthan, India
- <sup>c</sup> Mechanical Engineering Department, National Institute of Technology, Uttarakhand, Srinagar, Garhwal 246174, India
- <sup>d</sup> Mechanical Engg. Dept., Government Engineering College, Bharatpur 321001, India
- <sup>e</sup> Mechanical Engg. Dept., K J Somaiya College of Engineering, Mumbai 400007, India
- <sup>f</sup> Mechanical Engg. Dept., Swami Keshvanand Institute of Technology Management, Gramothan 302021, India

Received 9 March 2021, Revised 25 March 2021, Accepted 31 March 2021, Available online 23 April 2021.

Show less  Outline |  Share  Cite<https://doi.org/10.1016/j.matpr.2021.03.734>

Get rights and content

## Abstract

Current research work emphasis on the mechanical and tribological characteristics of the graphite reinforced AA7075 alloy composite. The samples were developed with various proportions (0, 1, 3, 5, and 7 wt%) of Gr particulate in Al alloy matrix using the high vacuum casting machine. The physical and mechanical characterization like density, void content, hardness, impact strength, flexural strength, and compressive strength were experimentally estimated. The dry sliding wear performance of the composite specimens was also estimated. The various samples were ranked based on the wear rate performance using the Taguchi method. The experimental results reveal